



### **GENERAL**

Highest quality sink formed of #18 gauge, type 304 (18-8) nickel bearing stainless steel. Top mount.

### **DESIGN FEATURES**

Bowl Depth: See chart below.

Coved Corners: 1-3/4" vertical and horizontal radius. Bowl Recess: 3/16" below outside edge of sink.

Finish: Exposed surfaces are hand blended to a lustrous

satin finish.

Underside: Fully undercoated to dampen sound and prevent

condensation.


## **OTHER**

Drain Opening: 3-1/2".

These sinks comply with ASME 112.19.3.



This sink is listed by the International Association of Plumbing and Mechanical Officials as meeting the requirements of the Uniform Plumbing Code.



# **SINK DIMENSIONS (INCHES)\***

| II Ohamad                | Outal Otto                       | Overall |                                | Inside Bowl |                                |      | Cutout in<br>Countertop<br>(11/2" Radius |                    | 8.0::              | 31/2"        |
|--------------------------|----------------------------------|---------|--------------------------------|-------------|--------------------------------|------|--|--------------------|--------------------|--------------|
| U-Channel<br>Model       | Quick-Clip <sup>®</sup><br>Model | L       | W                              | L           | W                              | D    | ` Cor                                    | ners)              | Minimum<br>Cabinet | Drain        |
| Number                   | Number                           | Α       | В                              | C           | D                              | E    | L  | W                  | Size               | Opening      |
| LFR1313                  | LFRQ1313                         | 13      | 13                             | 10          | 10                             | 75/8 | 123/8                                    | 123/8              | 18                 | Centered     |
| LFR1515                  | LFRQ1515                         | 15      | 15                             | 12          | 12                             | 75/8 | 14 <sup>3</sup> /8                       | 143/8              | 18                 | Centered     |
| LFR1717                  | ı                                | 17      | 171/2                          | 14          | 14                             | 75/8 | 16 <sup>3</sup> /8                       | 16 <sup>7</sup> /8 | 21                 | Centered     |
| LFR1915                  | LFRQ1915                         | 19      | 15                             | 16          | 11 <sup>1</sup> / <sub>2</sub> | 75/8 | 18 <sup>3</sup> /8                       | 143/8              | 24                 | Centered     |
| LFR1918                  | LFRQ1918                         | 19      | 18                             | 16          | 131/2                          | 75/8 | 18 <sup>3</sup> /8                       | 173/8              | 24                 | Centered     |
| LFR2519                  | LFRQ2519                         | 25      | 191/2                          | 21          | 15 <sup>3</sup> / <sub>4</sub> | 75/8 | 243/8                                    | 187/8              | 30                 | Centered     |
| <b>&amp;</b> LFRAD151555 | -                                | 15      | 15                             | 12          | 12                             | 51/2 | 14 <sup>3</sup> /8                       | 143/8              | 18                 | Centered     |
| <b>خ</b> LFRAD191860     | -                                | 19      | 18                             | 16          | 131/2                          | 6    | 18 <sup>3</sup> /8                       | 173/8              | 24                 | Centered     |
| <b>LFRAD251955</b>       | -                                | 25      | 191/2                          | 21          | 15 <sup>3</sup> / <sub>4</sub> | 51/2 | 243/8                                    | 187/8              | 30                 | Off-centered |
| <b>LFRAD251960</b>       | _                                | 25      | 19 <sup>1</sup> / <sub>2</sub> | 21          | 15 <sup>3</sup> / <sub>4</sub> | 6    | 243/8                                    | 187/8              | 30                 | Off-centered |
| <b>LFRAD251965</b>       | -                                | 25      | 191/2                          | 21          | 153/4                          | 61/2 | 243/8                                    | 187/8              | 30                 | Off-centered |

<sup>\*</sup>Length is left to right. Width is front to back

SEE OTHER SIDE FOR PRODUCT DIMENSIONS.

THIS PRODUCT, AS CONSTRUCTED IS SUBJECT TO INTERPRETATION OF A.D.A. REQUIREMENTS. THE UNOBSTRUCTED KNEE SPACE REQUIRED TO SATISFY A.D.A. STANDARDS MAY NOT BE DESIRABLE.


ALL DIMENSIONS IN INCHES, TO CONVERT TO MILLIMETERS MULTIPLY BY 25.4.

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice.


This specification describes an Elkay product with design, quality and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.



THIS PRODUCT, AS CONSTRUCTED IS SUBJECT TO INTERPRETATION OF A.D.A. REQUIREMENTS. THE UNOBSTRUCTED KNEE SPACE REQUIRED TO SATISFY A.D.A. STANDARDS MAY NOT BE DESIRABLE.




Model LFR2519 Illustrated



Model LFRAD2519 Illustrated

# **U-Channel Type Mounting System**



Quick-Clip® Mounting System

