Halsey Taylor OVL-II Single Fountain Non-Filtered Non-Refrigerated Gray Model OVL-II EBP GRY BASIN

PRODUCT SPECIFICATIONS

Halsey Taylor OVL-II™ Single Fountain, Non-Filtered Non-Refrigerated Gray. Furnished with Double Bubbler™. Mechanical Front Bubbler Button activation. Product shall be Wall Mount (On-Wall), for Indoor applications, serving 1 station(s). Unit shall be lead-free design which is certified to NSF/ANSI 61 & 372 (lead free) and meets Federal and State low-lead requirements.

Order ID:	7434004661
Finish:	Gray Marblyte™ (GRY)
Power:	No Electrical Required
Bubbler Style:	Double Bubbler™
Activation by:	Mechanical Front Bubbler Button
Mounting Type:	Wall Mount (On-Wall)
Chilling Option:	Non-Refrigerated
Dimensions (L x W x H):	19-3/4" x 19" x 21-15/16"
Approx. Shipping Weight:	29 lbs.
Installation Location:	Indoor
No. of Stations Served:	1

- Mechanically-Activated bubbler continues to supply water in event of service disruptions.
- Exclusive Double Bubbler which projects two separate streams that converge to form a fuller, more satisfying drink.



AMERICAN PRIDE. A LIFETIME TRADITION.

Like your family, the Elkay family has values and traditions that endure. For almost a century, Elkay has been a family-owned and operated company, providing thousands of jobs that support our families and communities.



Included with Product: Fountain PRODUCT COMPLIANCE

ADA & ICC A117.1 Buy American Act NSF/ANSI 61 & 372 (lead free)





Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.

Installation Instructions (PDF) - 97638C Installation Instructions (PDF) - 97459C

Water Systems are warranted for 12 months from date of installation. Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty. Warranty (PDF)

OPTIONAL ACCESSORIES

HWF172 - WaterSentry VII Filter Kit (Coolers + Fountains)	
MPW100 - In Wall Carrier (Single)	
APHT - Halsey Taylor Access Panel	
97446C - Bubbler Kit Vandal-Resistant	

PART:	_QTY:
PROJECT:	
CONTACT:	
DATE:	
NOTES:	
APPROVAL:	

In keeping with our policy of continuing product improvement, Halsey Taylor reserves the right to change product specifications without notice. Please visit Halseytaylor.com for the most current version of Halsey Taylor product specification sheets. This specification describes a Halsey Taylor product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

OPERATION OF QUICK CONNECT FITTINGS **INSTALLER NOTE** 3/8" O.D. TUBE CONNECT COLD WATER SUPPLY 1/4" O.D. TUBE WATER INLET This drinking fountain is furnished with a bubbler **BUILDING WATER** SIMPLY PUSH IN TUBE TO ATTACH TUBE IS SECURED IN POSITION PUSH IN COLLET TO RELEASE TUBE and valve including all connecting fittings which are manufactured of completely lead free material. • + 4407 Shut off valve (not furnished) to accept 3/8" O.D. 777/ - 777/ unplated copper tube. ㅁ PUSHING TUBE IN BEFORE PULLING IT OUT HELPS TO RELEASE TUBE NOTE: WATERFLOR SERVICE STOP (NOT FURNISHED) DIRECTION 19-3/4" 18-3/8 (502mm) (467mm) (16mm) ORIFICE 1-1/4" I.P.S. WASTE (LEFT OR RIGHT). WASTE IS SHOWN IN WALL, BUT MAY TO RIM -1-5/8" (41mm) 21-15/16" (557mm) BE BEHIND WALL 28-3/4" WASTE OPTIONAL ACCESS PANEL AND FRAMING NOT SHOWN (730mm) 9" SQ 33-15/16" (863mm) (229mm) 21-1/2" (546mm) SUPPLY RECOMMENDED SHUT OFF 3/8" I.P.S. SUPPLY (LEFT OR RIGHT) 16-1/2" AP99 ACCESS PANEL 27" (686mm) (419mm) WASTE ELBOW, BY OTHERS EXTENSION AND TRAP BY OTHERS (OPTIONAL) NOTE REQUIREMENT 13-3/4" (349mm) INSTALLATION CAN BE MADE THRU OPTIONAL FRONT ACCESS PANEL OR FROM REAR ACCESS FINISHED FLOOR SUPPORT PREPARATION NOTE (406mm) WALL PLATE MUST BE SUPPORTED SECURELY. ADD FIXTURE SUPPORT CARRIER IF WALL WILL NOT PROVIDE ADEQUATE SUPPORT. 9-3/4" (248mm) (203mm) 5-1/4" (133mm) 5-1/4" (133mm) 1-1/4" 1/4" (8mm) DIA. HOLES FOR MOUNTING PLATE TO WALL (32mm)BACK PANEL SURFACE MOUNTING 1-1/4" (32mm) I.P.S. WASTE (LEFT OR RIGHT) WASTE IS SHOWN IN WALL, BUT MAY BE BEHIND WALL. 3/8" (10mm) DIA. HOLES FOR MOUNTING PLATE TO WALL (10) SUPPLY 3/8" I.P.S. LEFT OR RIGHT SIDE 7-7/8" (200mm) 43-5/8" (1108mm) 烘光 (203mm) 29-1/4" (743mm) 28-3/4" 26-1/2" (673mm) (730mm) (203mm) FRAMING REQ'D 14-1/4" WHEN OPTIONAL AP99 ACCESS PANEL IS USED (362mm) FINISHED FLOOR

In keeping with our policy of continuing product improvement, Halsey Taylor reserves the right to change product specifications without notice. Please visit Halseytaylor.com for the most current version of Halsey Taylor product specification sheets. This specification describes a Halsey Taylor product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.