# Halsey Taylor Explosion Proof Floor Mount Cooler Non-Filtered 8 GPH Stainless

Model XP8W

# PRODUCT SPECIFICATIONS

Halsey Taylor Explosion Proof Floor Mount Cooler, Non-Filtered 8 GPH Stainless. Chilling Capacity of 8.0 GPH (gallons per hour) of 50° F drinking water, based on 80° F inlet water and 90° F ambient, per ASHRAE 18 testing. Furnished with Double Bubbler. Mechanical Top Bubbler Button activation. Product shall be Floor Mount/Freestanding, for Indoor applications, serving 1 station(s). Unit shall be certified to UL 399 and CAN/CSA C22.2 No. 120. Unit shall be lead-free design which is certified to NSF/ANSI 61 & 372 (lead free) and meets Federal and State low-lead requirements.

| Order ID:  | 8221080883                    |
|--|-------------------------------|
| Finish:  | Stainless Steel               |
| Power:   | 115V/60Hz                     |
| Bubbler Style:   | Double Bubbler                |
| Activation by:   | Mechanical Top Bubbler Button |
| Mounting Type:   | Floor Mount/Freestanding      |
| Chilling Option*:  | 8.0 GPH                       |
| Full Load Amps   | 5                             |
| Rated Watts:   | 370                           |
| Dimensions (L x W x H):  | 16" x 13-1/4" x 40"           |
| Approx. Shipping Weight:   | 84 lbs.                       |
| Installation Location:   | Indoor                        |
| No. of Stations Served:  | 1                             |
| *Based on 80° F inlet water & 90° F ambient air temp for 50° F chilled |                               |

\*Based on 80° F inlet water & 90° F ambient air temp for 50° F chilled drinking water.

Mechanically-Activated bubbler continues to supply water in

 Exclusive Double Bubbler which projects two separate streams that converge to form a fuller, more satisfying drink.

# COOLING SYSTEM

event of service disruptions.

- Compressor: Hermetically-sealed, reciprocating type, single phase. Sealed-in lifetime lubrication.
- Condenser: Fan cooled, copper tube with aluminum fins. Fan motor is permanently lubricated.
- Cooling Unit: Combination tube-tank type. Continuous copper tubing with is fully insulated with EPS foam that meets UL requirements for self-extinguishing material.
- Refrigerant Control: Refrigerant R-134a is controlled by accurately calibrated capillary tube.
- Temperature Control: Easily accessible enclosed adjustable thermostat is factory preset. Requires no adjustment other than for altitude requirements.



AMERICAN PRIDE. A LIFETIME TRADITION.
Like your family, the Elkay family has values and traditions that
endure. For almost a century, Elkay has been a family-owned and
operated company, providing thousands of jobs that support our
families and communities.



Included with Product: Water Cooler

### PRODUCT COMPLIANCE

Buy American Act CAN/CSA C22.2 No. 120 NSF/ANSI 61 & 372 (lead free) UL 399



## Installation Instructions (PDF)

5 Year Limited Warranty on the refrigeration system of the unit. Electrical components and water system are warranted for 12 months from date of installation. Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty.


Warranty (PDF)

# **OPTIONAL ACCESSORIES**

HWF172 - WaterSentry VII Filter Kit (Coolers + Fountains)

| PART:     | QTY: |
|-----------|------|
| PROJECT:  |      |
| CONTACT:  |      |
| DATE:     |      |
| NOTES:    |      |
| APPROVAL: |      |

In keeping with our policy of continuing product improvement, Halsey Taylor reserves the right to change product specifications without notice. Please visit Halseytaylor.com for the most current version of Halsey Taylor product specification sheets. This specification describes a Halsey Taylor product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.



- A = Recommended water supply location 3/8" (10mm) O.D. unplated copper tube connect stub 1-1/2" (38mm) out from wall shut off valve by others. B = Recommended location for waste outlet 1-1/4" (32mm) O.D. drain. C = 1-1/4" (32mm) trap not furnished.
  D = Electrical outlet location.

- E = Insure proper ventilation by maintaining 4" (102mm) minimum clearance from cabinet louvers to wall.
  F = Wall screw holes.
  G = 2 X 4 blocking.

In keeping with our policy of continuing product improvement, Halsey Taylor reserves the right to change product specifications without notice. Please visit Halseytaylor.com for the most current version of Halsey Taylor product specification sheets. This specification describes a Halsey Taylor product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.