

# Halsey Taylor HydroBoost Vandal-Resistant Bottle Filling Station & Single ADA Cooler Non-Filtered 8 GPH Stainless

## **Model HTHBHVR8-NF**

### PRODUCT SPECIFICATIONS

Halsey Taylor HydroBoost® Vandal-Resistant Bottle Filling Station & Single ADA Cooler Non-Filtered 8 GPH Stainless. Chilling Capacity of 8.0 GPH (gallons per hour) of 50° F drinking water, based on 80° F inlet water and 90° F ambient, per ASHRAE 18 testing. Features shall include Green Counter™, Laminar Flow, Real Drain, Vandal Resistant. Furnished with Vandal Resistant bubbler. Electronic Bottle Filler Button With Mechanical Front Bubbler Button activation. Product shall be Wall Mount (On Wall), for Indoor + Outdoor applications, serving 1 station(s). Unit shall be certified to UL 399 and CAN/CSA C22.2 No. 120. Unit shall be lead-free design which is certified to NSF/ANSI 61 & 372 (lead free) and meets Federal and State low-lead requirements.

Special Features:	Green Counter™, Laminar Flow, Real
	Drain, Vandal Resistant
Finish:	Stainless Steel
Power:	115V/60Hz
Bubbler Style:	Vandal Resistant
Activation by:	Electronic Bottle Filler Button With
	Mechanical Front Bubbler Button
Mounting Type:	Wall Mount (On Wall)
Chilling Option*:	8.0 GPH
Full Load Amps	1
Rated Watts:	370
Dimensions (L x W x H):	18" x 18-5/8" x 38-13/16"
Approx. Shipping Weight:	85 lbs.
Installation Location:	Indoor + Outdoor
No. of Stations Served:	1
*Based on 80° F inlet water & 90° F ambient air temp for 50° F chilled	

- Mechanically-Activated bubbler continues to supply water in event of service disruptions.
- Green Counter: Informs user of number of 20 oz. plastic water bottles saved from waste.
- Laminar flow provides clean fill with minimal splash.
- · Real Drain System eliminates standing water.

#### **COOLING SYSTEM**

drinking water.

- Compressor: Hermetically-sealed, reciprocating type, single phase. Sealed-in lifetime lubrication.
- Condenser: Fan cooled, copper tube with aluminum fins. Fan motor is permanently lubricated.
- Cooling Unit: Combination tube-tank type. Continuous copper tubing with is fully insulated with EPS foam that meets UL requirements for self-extinguishing material.
- Refrigerant Control: Refrigerant R-134a is controlled by accurately calibrated capillary tube.
- Temperature Control: Easily accessible enclosed adjustable thermostat is factory preset. Requires no

PART:	QTY:
PROJECT:	
CONTACT:	
DATE:	
NOTES:	
APPROVAL:	



#### AMERICAN PRIDE. A LIFETIME TRADITION.

Like your family, the Elkay family has values and traditions that endure. For almost a century, Elkay has been a family-owned and operated company, providing thousands of jobs that support our families and communities.



Included with Product: Water Cooler (CLR-HTHBHVR8-NF)

Bottle Filler (HVRHTHB-NF)

▼ Ships in multiple boxes.

#### PRODUCT COMPLIANCE

ADA & ICC A117.1

**Buy American Act** 

CAN/CSA C22.2 No. 120

GreenSpec®

NSF/ANSI 61 & 372 (lead free)

UL 399







Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.

#### Installation Instructions (PDF)

5 Year Limited Warranty on the refrigeration system of the unit. Electrical components and water system are warranted for 12 months from date of installation. Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty.

Warranty (PDF)

### **OPTIONAL ACCESSORIES**

HWF3000 - WaterSentry Plus Filter Kit (Bottle Fillers)
MLP100 - Accessory - In Wall Carrier (Single) for single EZ, LZ,

MLP100 - Accessory - In Wall Carrier (Single) for single EZ, LZ, EMABF, LMABF, VRC, LVRC models

98324C - Accessory - Cane Apron for HAC, HVR, EMABF & VRC Models (Stainless)

In keeping with our policy of continuing product improvement, Halsey Taylor reserves the right to change product specifications without notice. Please visit Halseytaylor.com for the most current version of Halsey Taylor product specification sheets. This specification describes a Halsey Taylor product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

will connect through pre-punched hole in basin.

# Halsey Taylor HydroBoost Vandal-Resistant Bottle Filling Station & Single ADA Cooler Non-Filtered 8 GPH Stainless **Model HTHBHVR8-NF**

direction

adjustment other than for altitude requirements.

#### IMPORTANT! INSTALLER PLEASE NOTE : OPERATION OF QUICK CONNECT FITTINGS Simply push in |Tube is secured |Push in collet to This water cooler has been designed and built to provide water to the user which tube to attach in position release tube has not been altered by materials in the cooler waterways. The grounding of electrical equipment such as telephone, computer, etc. to water lines is a common procedure. The grounding may be in the building but may also occur away from the building. This grounding can cause electrical feedback into a water cooler creating an electrolysis which creates a metallic taste or causes an increase in the metal content of the water. Pushing tube in before This condition is avoidable by installing the cooler using the proper materials as shown 1/4" O.D. tube 3/8" O.D. Tube connect Building water pulling it out helps to water inlet to cold water supply release tube inlet NOTICE cooler This water cooler must be connected to the water supply using a dielectric coupling. The cooler is furnished with a non-metallic strainer which meets this requirement. The drain trap which is provided by the installer should also be plastic to completely isolate the cooler from the building plumbing system. Bottle filler unit on bracket attached to wall by 6 holes (as shown). Water and electrical Servicé stop NOTE: Waterflow (Not furnished)

These products are designed to operate on 20 psi to 105 psi supply line pressure. 18-5/8" 16-5/16 (414mm) (472mm) Ø 5/16" 5-1/8" (8mm) (178mm) (178mm) MOUNTING (131mm) HOLES (3PL) 51-1/8" (1298mm) HANGER 18-1/2 BRACKET (470mm) 2-5/8" 1/4" 1/2" (6mm x 13mm) (66mm) OBROUND HOLE (5PL) 1-1/4" 1-1/4" (1219mm) (32mm) <sub>I</sub> (32mm) E 0 4-9/16 E-33-1/16" (116mm) (840mm) ORIFICE 49-1/2" E (1257mm) HEIGHT (203mm) 3/4" (18mm) 2-1/2" 7-1/4" (185mm) (64mm) 31-15/16" C D-31" (811mm) (788mm) RIM ( (1) HEIGHT (635mm) 2-7/16 1-1/2" (63mm) (686mm) 38mm) 3-1/2 (543mm) 2-9/16" (89mm) 4-1/2" (65mm) REQUIREMENT 6-1/4" 18-3/8" 13-7/8" (352mm) (159mm) (114mm) 12-5/16" (313mm) (467mm) 6-3/4" 127mm) (254mm) (171mm)FINISHED FLOOR FINISHED FLOOR REDUCE HEIGHT BY 3" FOR INSTALLATION OF CHILDREN'S ADA COOLER

A = Recommended Water Supply location. Shut-off Valve (not furnished) to accept 3/8" O.D. unplated copper tube. Up to 3" (76mm) maximum out from wall. B = Recommended Waste Outlet location. To accommodate 1-1/4" nominal drain. Drain stub 2" (51mm) out from wall.

C = 1-1/4" Trap (not furnished)

LEGEND:

D = Electrical Supply (3) Wire Recessed Box Duplex Outlet.

E = Insure proper ventilation by maintaining 6" (152mm) minimum clearance from cabinet louvers to wall.

F = 7/16" (11mm) Bolt Holes for fastening to wall.

Note: New Installations Must Use Ground Fault Circuit Interrupter (GFCI). It is highly recommended that the circuit be dedicated and the load protection be sized for 20 amps.

In keeping with our policy of continuing product improvement, Halsey Taylor reserves the right to change product specifications without notice. Please visit Halseytaylor.com for the most current version of Halsey Taylor product specification sheets. This specification describes a Halsey Taylor product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.